



Specifications

Payload	Agriculture Products
----------------	----------------------

Dimensions

Length	50' 15.24m
Width	102" (2.59m)
Overall Height	13' (3.96m) to Top of Arch
Volume	3,210 ft ³ (118.9 yd ³)
Weight	9,797 kg (21,598.7 lbs)

Running Gear

Axles/Suspensions	Primary: SAF CBX Lift or Steers: Titan ParaMAX 25,000lb
ABS	2S1M Meritor Wabco
Brake Type	Disc
Tires	Michelin
Landing Gear	Holland Mark 5

Body

Side Panels	Aluminum Patented THINWALL® Horizontal Hollow-Core Extruded Panels
Flooring	Keith® Walking Floor® - Running Floor II, 2195 3/16" Pressure Seal
Mud flaps	Black Rubber with Titan Logo
Lights	LED - Truck Lite
Rear Door	Van, Solid, Cathedral
Bumper	No Bumper Due to Internal Rear Hopper



TITAN 50' 4 Axle THINWALL® Walking Floor (S.P.I.F.#3)



TAILOR YOUR TITAN

to suit your personal preference and application



24" Catwalk



Front Man Door



Front Ladder Driver Side



All Aluminum Chassis



Fold Down Steps



Internal Rear Hopper



Keith® Walking Floor®



Fenders Over
Primary and Steer

KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside AND outside for end-to-end strength.
- KEITH® WALKING FLOOR® • Steel coupler assembly with bolt in kingpin
- Aluminum frame/floor assembly • Tapered Top Rail • Single top cross tube

HEAD OFFICE

1129 Hwy #3, R.R. #3, Delhi, Ontario, Canada N4B 2W6
Tel: 519-688-4826 • Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation  www.titantrailers.com

