



Specifications

Payload Agriculture Products

Dimensions

Length	53' (16.1m)
Width	102" (2.59m)
Overall Height	13' 4" (4.06m) approx. to Top of Tarp Header
Volume	3,834 ft ³ (142 yd ³)
Weight	11,162 kg (24,607.99 lbs)

Running Gear

Axles/Suspensions	Primary: SAF CBX 25/30 245 Lift or Steers: Titan ParaMAX 25,000lb
ABS	4S3M
Brake Type	Disc
Tires	Goodyear
Landing Gear	Holland Mark 5

Body

Side Panels	Aluminum Patented THINWALL® Horizontal Hollow-Core Extruded Panels
Flooring	Keith® Walking Floor® - 2203(1976) 3 1/2', 1212 Seal
Mud flaps	Black Rubber with Titan Logo
Lights	LED - Truck Lite
Rear Door	Van, Solid
Bumper	Aluminum, Flush, Narrow



TITAN 53' 5 Axle THINWALL® Walking Floor (S.P.I.F.#4)



TAILOR YOUR TITAN

to suit your personal preference and application



Front Man Door



Flip Step



24" Catwalk



All Aluminum Chassis



Keith® Walking Floor®



Front Driver Side Ladder



Top Cross Tubes

KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside AND outside for end-to-end strength.
- KEITH® WALKING FLOOR® • Steel coupler assembly with bolt in kingpin
- Aluminum frame/floor assembly • Offset top rail • Single top cross tube

HEAD OFFICE

1129 Hwy #3, R.R. #3, Delhi, Ontario, Canada N4B 2W6
Tel: 519-688-4826 • Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation  www.titantrailers.com

