



TITAN 50' 7 Axle THINWALL® Walking Floor



Specifications

Payload	Feed Products and Grains
----------------	--------------------------

Dimensions

Length	50' (15.24m)
Width	102" (2.59m)
Overall Height	153 1/8" (3.889m) approx. to top of arched header at front approx. 143 3/16" (3.6369m) to top of sidewalls at front
Volume	2,979 ft ³ (110.3 yd ³)
Weight	X kg (x lbs)

Running Gear

Axles/Suspensions	Primary: HT300 @ 45" Lifts: Front - HT250, 2nd from front - HT250 w/rear HT300
ABS	2S2M Meritor Wabco
Brake Type	Drum
Tires	Goodyear
Landing Gear	Holland Mark 5

Body

Side Panels	Aluminum Patented THINWALL® Horizontal Hollow-Core Extruded Panels
Flooring	Keith® Walking Floor® Running Floor II - 3.5" Diameter Cylinders - 10" Stroke - 2190 (1975) 3.5" 1212 Seals - T-Block Rear
Mud flaps	Black Rubber with Titan Logo
Lights	LED - Truck Lite
Rear Door	Top Hinge Overslung, Tipper/Hydraulic, Air Release
Bumper	Wide, Flush, Aluminum



TITAN 50' 7 Axle THINWALL® Walking Floor



TAILOR YOUR TITAN

to suit your personal preference and application



Tire Carrier



24" Catwalk



12"x12" Overload Chute
Centered on Rear Tailgate



Front Access Door with
Flip Down Step



Front Ladder Drivers Side



Back Ladder Drivers Side
on Rear Door



Tow Shackles



Keith® Walking Floors®



All Aluminum Chassis



Tow Hooks

KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside AND outside for end-to-end strength.
- KEITH® WALKING FLOOR® • Steel coupler assembly with bolt in kingpin
- Aluminum frame/floor assembly

HEAD OFFICE

1129 Hwy #3, R.R. #3, Delhi, Ontario, Canada N4B 2W6
Tel: 519-688-4826 • Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation  www.titantrailers.com

