

TITAN 40' 3 Axle THINWALL® Hopper Open Top

Specifications

Payload	Grain & Bulk Commodities
----------------	--------------------------

Dimensions

Length	40' (12.2m)
Width	102" (2.59m)
Overall Height	134.5" (3.4m)
Side Height	76 3/8" (1.94m)
Upper Slope Angle	30°
Level Volume	1,675 ft³ (62 yd³ • 1,346 bu.)
Heaped Volume	1,831 ft³ (67.8 yd³ • 1,471.3 bu.)
Weight Super Singles (w/o tarp)	12,230 lb (5,547.4 kg)
Weight Duals (w/o tarp)	12,800 lb (5,806 kg)

Running Gear

Axles/Suspensions	SAF CBX 25/30
ABS/Brake System	2S/2M Meritor Wabco
Brake Type	Disc
Tires	Bridgestone
Landing Gear	Jost AX141.G8.17 Aluminum



*trailer shown has high ground clearance hoppers.



Body

Side Panels	14" (356mm) tall heavy duty aluminum; patented THINWALL horizontal hollow-core extruded panels
Top Rail	Integrated tarp latch plate extruded into THINWALL top panel
Hoppers	Front Double Door: 28" x 24" Middle Door: 28" x 24" Rear Door: 33" x 30" (rear discharge shoot)
Mud flaps	Black Rubber with Titan Logo
Top Crossmember	9" (23cm) rise integrated arched top crossmembers
Lights	Standard Light Package



TITAN 40' 3 Axle THINWALL® Hopper Open Top



TAILOR YOUR TITAN

to suit your personal preference and application



Disc Brakes



Aluminum Coupler



Debris Shield



High Ground
Clearance Hoppers



Arched Top Cross
Members & Vented
Divider Walls



Integrated Tarp Latch Plate



Rear Discharge Chute



Jost All Aluminum
Landing Gear

KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside & outside for end-to-end strength
- 100% welded, all aluminum, rivet free, unibody construction provides an industry leading strength to weight ratio
- Perfectly smooth, rivet free lower hoppers provides superior cleanout
- Closed body design eliminates mud/snow build-up under the trailer body

HEAD OFFICE

1129 Hwy #3, R.R. #3 • Delhi, Ontario, Canada N4B 2W6
Tel: 519-688-4826 Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation  www.titantrailers.com

