



TITAN 28' 4 Axle B-Train LEAD - 28' 6" 3 Axle PUP THINWALL® Trailer



Specifications

Payload Grain & Bulk Commodities

Dimensions

Length
Lead Box: 28' (8.5m)
Pup Box: 28'6" (8.7m)
Overall Length: 60'5" (18.4m)

Width 102" (2.59m)

Overall Height 144.5" (3.67 m)

Side Height 82 3/8" (2.09 m)

Upper Slope Angle 30°

Level Volume
Lead: 1,299 ft³ (48.1 yd³ • 1,043.8 bu.)
Pup: 1,341 ft³ (49.7 yd³ • 1,077.6 bu)
TOTAL: 2,640 ft³ (97.8 yd³ • 2,121.4 bu)

Heaped Volume
Lead: 1,408 ft³ (52.1 yd³ • 1,131.4 bu.)
Pup: 1,450 ft³ (53.7 yd³ • 1,165.1 bu.)
TOTAL: 2,858 ft³ (105.8 yd³ • 2,296.5 bu)

Weight Super Singles (w/o tarp) 25,496.5 lb (11,565 kg)

Weight Duals (w/o tarp) 26,825.8 lb (12,168 kg)

Running Gear

Axles/Suspensions **Primary:** SAF CBX 25/30
Lifts: SAF CBX 25/30 with Titan Parallel Lift Kit

ABS/Brake System 2S2M Meritor Wabco

Brake Type Disc

Tires Goodyear or Michelin

Landing Gear Jost AX141.G8.17 Aluminum

Body

Side Panels 14" (356mm) tall heavy duty aluminum; patented THINWALL horizontal hollow-core extruded panels

Top Rail Integrated tarp latch plate extruded into THINWALL top panel

Hoppers **LEAD:** 28" x 24"
PUP: Front hopper 26" x 20" (open sideways),
 Rear hopper 28" x 24"

Mud flaps Black Rubber with Titan logo

Top Crossmember 9" (23cm) rise integrated arched top crossmembers

Lights Standard LED Package includes interior & exterior hopper lights, 5 upper & lower sidewall lights, back-up lights and high mount brake lights



TITAN 28' 4 Axle B-Train LEAD - 28' 6" 3 Axle PUP THINWALL® Trailer



TAILOR YOUR TITAN

to suit your personal preference and application



Super Singles



Arched Top Cross Members
& Vented Divider Walls



Exterior Light Package



Interior Lighting Package



Tire Air Inflation System



Jost All Aluminum
Landing Gear



Aluminum Coupler



Integrated Tarp Latch Plate



Aluminum Fifth Wheel with
Aluminum Lead Frame



Titan Contoured Fenders

KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside & outside for end-to-end strength
- 100% welded, all aluminum, rivet free, unibody construction provides an industry leading strength to weight ratio
- Perfectly smooth, rivet free lower hoppers provides superior cleanout
- Closed body design eliminates mud/snow build-up under the trailer body

HEAD OFFICE

1129 Hwy #3, R.R. #3 • Delhi, Ontario, Canada N4B 2W6
Tel: 519-688-4826 Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation  www.titantrailers.com

