

TITAN 50' 7 Axle THINWALL® Walking Floor



Specifications

Payload

Feed Products and Grains

Dimensions

Length	50' (15.24m)
Width	102" (2.59m)
Overall Height	153 1/8"(3.889m) approx. to top of arched header at front approx. 143 3/16" (3.6369m) to top of sidewalls at front
Volume	2,979 ft ³ (110.3 yd ³)
Weight	12,900 kg (28,439.6 lbs)

Running Gear

Axles/Suspensions	Primary: HT300 @ 45" Lifts: Front - HT250, 2nd from front - HT250 w/rear HT300
ABS	2S2M Meritor Wabco
Brake Type	Drum
Tires	Goodyear
Landing Gear	Holland Mark 5

Body	
Side Panels	Aluminum Patented THINWALL [®] Horizontal Hollow-Core Extruded Panels
Flooring	Keith [®] Walking Floor [®] Running Floor II - 3.5" Diameter Cylinders - 10" Stroke - 2190 (1975) 3.5" 1212 Seals - T-Block Rear
Mud flaps	Black Rubber with Titan Logo
Lights	LED - Truck Lite
Rear Door	Top Hinge Overslung, Tipper/Hydraulic, Air Release
Bumper	Wide, Flush, Aluminum

Strength Through Innovation 🌞 www.titantrailers.com



TITAN 50' 7 Axle THINWALL® Walking Floor



TAILOR YOUR TITAN

to suit your personal preference and application



Tire Carrier





Top Crossmembers

& Tarp Bows



12"x12" Overload Chute Centered on Rear Tailgate



Keith[®] Walking Floors[®]



Front Access Door with Flip Down Step



All Aluminum Chassis



Front Ladder Drivers Side



Tow Hooks

000

KEY FEATURES

Back Ladder Drivers Side

on Rear Door

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside AND outside for end-to-end strength.
- KEITH® WALKING FLOOR® Steel coupler assembly with bolt in kingpin
- Aluminum frame/floor assembly

HEAD OFFICE

1129 Hwy #3, R.R. #3, Delhi, Ontario, Canada N4B 2W6 Tel: 519-688-4826 • Fax: 519-688-6453 • e-mail: info@titantrailers.com

Strength Through Innovation 👾 www.titantrailers.com