



# TITAN 60'5" 5 Axle Unibody Hopper B-Train Open Top THINWALL® Trailer

Now Available in  
Standard or  
Polished Finish

## Specifications

Payload	Grain & Bulk Commodities
---------	--------------------------

## Dimensions

Length	Lead Box: 28' (8.5m) Pup Box: 28'6" (8.7m) Overall Length: 60'5" (18.4m)
Width	102" (2.59m)
Overall Height	143" (3.6m)
Side Height	82 3/8" (2.1m)
Upper Slope Angle	30°
Level Volume	Lead: 1,341 ft <sup>3</sup> (49.7 yd <sup>3</sup> • 1,078 bu.) Pup: 1,350 ft <sup>3</sup> (50 yd <sup>3</sup> • 1,084 bu.) TOTAL: 2,691 ft <sup>3</sup> (99.7 yd <sup>3</sup> • 2,162 bu.)
Heaped Volume	Lead: 1,450 ft <sup>3</sup> (53.7 yd <sup>3</sup> • 1165 bu.) Pup: 1,461 ft <sup>3</sup> (54.1 yd <sup>3</sup> • 1173.8 bu.) TOTAL: 2,911 ft <sup>3</sup> (107.8 yd <sup>3</sup> • 2,338.8 bu.)
Weight without tarp	21,067 lb (9,556 kg)
Weight with tarp	21,398 lb (9,706 kg)

## Running Gear

Axles/Suspensions	Primary: Hendrickson Intraax AAL25K(Lead), AAT25K(Pup)
ABS/Brake System	2S2M Meritor Wabco
Brake Type	Drum
Tires	Goodyear
Landing Gear	Jost AX151.G8.17 Aluminum



## Body

Side Panels	14" (356mm) tall heavy duty aluminum; patented THINWALL horizontal hollow-core extruded panels
Top Rail	Integrated tarp latch plate extruded into THINWALL top panel
Hoppers	Lead: Double hopper 22" x 22" Pup: Double hopper 22" x 22"
Mud flaps	Black Rubber with Titan logo
Top Crossmember	9" (23cm) rise integrated arched top crossmembers
Lights	Standard LED Package includes interior & exterior hopper lights, 5 upper & lower sidewall lights, back-up lights and high mount brake lights, 4 lights down rear posts on pup







# TITAN 60'5" 5 Axle Unibody Hopper B-Train - Open Top THINWALL® Trailer



## TAILOR YOUR TITAN

to suit your personal preference and application




Optional Super Singles



Optional Disc or Drum  
Brakes



Optional Exterior Light  
Package



Optional Interior Lighting  
Package



Standard Arched Top Cross  
Members & Vented Divider Walls



Standard Jost Aluminum  
Landing Gear



Standard Aluminum  
Coupler



Standard Integrated Tarp  
Latch Plate



Standard Aluminum Fifth  
Wheel with Aluminum  
Lead Frame



Standard Stainless Steel  
Fenders

## KEY FEATURES

- The patented THINWALL® panel features a horizontal tongue-in-groove joint that allows 100% machine welding inside & outside for end-to-end strength
- 100% welded, all aluminum, rivet free, unibody construction provides an industry leading strength to weight ratio
- Perfectly smooth, rivet free lower hoppers provides superior cleanout
- Closed body design eliminates mud/snow build-up under the trailer body

### HEAD OFFICE

1129 Hwy #3, R.R. #3 • Delhi, Ontario, Canada N4B 2W6

Tel: 519-688-4826 Fax: 519-688-6453 • e-mail: [info@titantrailers.com](mailto:info@titantrailers.com)



Strength Through Innovation



[www.titantrailers.com](http://www.titantrailers.com)